

MATERIAL SPECIFICATION



FITNESS



Solid construction made of black steel S235JR, cleaned in the sandblasting process. Protected against corrosion by galvanizing and powder coating with polyester paint QUALICOAT attested.



Plates made of colourful triple layered polyethylene. HDPE 15 mm thick in the highest quality, totally dampproof and resistant to UV.



Back support and seats made of colourful triple layered polyethylene. HDPE 15 mm thick in the highest quality, totally damp-proof and resistant to UV.



Bumpers made of durable polyurethane.



Plate made of anodized aluminium placed on a handle made of polyamide. The instruction contains following information: • Which muscles are

- being trainedNorm number
- Emergency numbers.



Self-aligning roller bearings. Bearings in casings securing them from water access. The Joints are maintenancefree and don't require periodic lubrication.



Air brake. Mechanism increasing the resistance with the increase of rotation speed. Side panels and pedals made of stainless steel.



Connecting elements like screws, nuts, washers made of stainless steel. Vandal-proof screw plugs made of injection molded polyamide.



Anti-slip plate imade of 13 mm HPL, in the highest quality, totally damp-proof and resistant to UV.



Post endings finished with soft EPDM rubber.



Anti-slip anthracite 10 mm HPL platform plate with a veryhigh resistance to weather conditions and attrition.

