

Acti'Fit (technical specification)

J37103



1- The 102mm diameter posts are made of painted galvanised steel. The two-tone grey grained finish has a slightly undulating surface for increased scratch resistance.



2- The tubes are made of 40mm and 33mm diameter stainless steel, guaranteeing lasting durability and reliability of the equipment.



3- The tubes used for the Parallel bars and Suspension bars are made of electro-galvanized steel (diameter 34 mm) and stainless steel (diameter 40 mm), coated with epoxy paint. Electrogalvanization ensures corrosion resistance and provides a high quality finish. Stainless steel guarantees the longevity and robustness of the equipment over time.


The epoxy paint ensures better grip.



4- The caps are made of of painted aluminium (A) or rotary moulded polyethylene (B).



5- The fixing elements are made of painted aluminium.



6- The coloured panels are made from a 13mm thick compact material (HPL). Robust in construction, it has excellent weather and vandal resistance properties.





7- The Central Column seating is supported by a painted galvanized steel frame structure.



8- The Balancing board is fitted to a galvanized steel post, diameter 114 mm. A ball and socket joint ensures ease of movement.



9- The Punching bag, which is filled with EPDM granulates and polyurethane foam, is covered in a waterproof cotton canvas material. It is held up with small link stainless steel chains.



10-The Punching ball, which is filled with EPDM aggregates, is covered in a waterproof cotton canvas material.



11-The Runner rolling bars and surrounding frame structure are made of stainless steel.



12-The Rowing machine seat is made of rubber. Two ergonomic handles are provided on either side to ensure a firm hold while exercising.



13-The Coat Hook is made of polypropylene.





14-The stainless steel Tai Chi wheel rotation system is equipped with bearings.



15-The fixings are made of stainless or plated steel and protected by anti-vandalism polyamide caps.

