

Kanopé (technical specification)



1- The 95 x 95mm posts are made of painted galvanised steel, ensuring robustness and durability.



2- The caps are made of rotary moulded polyethylene.



3- The coloured panels are made from a 13mm thick compact material (HPL). Robust in construction, it has excellent weather and vandal resistance properties.



4- The platforms are made from a 12.5mm thick textured and non-slip compact material (HPL).



5- The tubes are made of 40mm diameter stainless steel, guaranteeing lasting durability and reliability of the equipment.



6- Injection moulded polyamide fixings connect the posts with the platforms and the various play features. They are non-toxic, flameproof and U.V. resistant. The thickness of the polyamide makes the equipment both strong and vandal resistant.





7- The 16mm diameter ropes are made of galvanised steel cable covered with polyester. The cables are linked together and held in place by injected polyamide spheres.



8- The net fittings are made of polyamide.


The fittings are composed of two distinct parts for ease of maintenance of individual strands.



9- The strap is made of 5 ropes linked together with aluminium pliers. Each rope, of 16mm diameter, is made up of galvanized steel cables covered in polypropylene.



10-The sliding surface is made of 2mm thick stainless steel, which is shaped, bent and rolled from one piece.



11-The porthole is made from 8mm thick methacrylate (PMMA).



12-The fixings are made of stainless or plated steel and protected by anti-vandalism polyamide caps.

